

Product datasheet

Specifications



current transformer TI 1000/5 A - for insulated flexible bar 65 x 32 mm

16483

⚠ Discontinued on: 17 Nov 2014

⚠ Discontinued

Main

Range	PowerLogic
Product Name	CT
Product Or Component Type	Current transformer
Secondary Current	5 A
Accuracy Class	Class 0.5 at 15 VA Class 1 at 20 VA Class 3 at 25 VA
[In] Rated Current	1000 A

Complementary

Current Transformer Type	Tropicalised for busbar
Current Transformer Ratio	1000/5
Maximum Safety Factor	5
[Ue] Rated Operational Voltage	< 720 V AC 50/60 Hz
Mounting Mode	Insulated locking screw
Mounting Support	Busbar
Width	Inner: 32 mm Outside: 90 mm
Height	Inner: 65 mm Outside: 90 mm
Depth	Outside : 87 mm
Net Weight	0.6 kg
Opening Of Bars	65 x 32
Sealing	With

Environment

Standards	VDE 0414 IEC 60044-1
Product Certifications	CE
Ip Degree Of Protection	IP20
Relative Humidity	95...100 %
Ambient Air Temperature For Operation	-25...60 °C

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
	Product out of China RoHS scope. Substance declaration for your information
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins