

LZX:PT78704

SOCKET FOR RELAYS

Technical data

SOCKET FOR RELAYS WITH 4 CO CONTACTS

General technical data	
Switching behavior	monostable
Design of the switching function	changeover switch
Design of the switching function positively driven	No
Reference code acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750	K
Reference code	
• acc. to IEC 81346-2:2009	U
• acc. to DIN EN 61346-2	U
Design of the relay operating mechanism	poled
Product component Plug-in socket	Yes
Auxiliary circuit	
Number of NC contacts	
• for auxiliary contacts	0
Number of NO contacts	
• for auxiliary contacts	0
Number of CO contacts	
• for auxiliary contacts	0
Connections/Terminals	
Type of electrical connection	screw-type terminals
Installation/ mounting/ dimensions	
Mounting type	standard rail
Height	75 mm
Width	27 mm
Depth	73.1 mm
Ambient conditions	
Ambient temperature	
• during operation	-40 ... +70 °C
Certificates/approvals	

General Product Approval			Declaration of Conformity	other
 UR	 VDE	 EAC	 EC/EU-Declaration of Conformity	Confirmation

Further information

Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/industrial-controls/catalogs
Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=LZX:PT78704
Cax online generator http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=LZX:PT78704
Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/en/ps/LZX:PT78704
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=LZX:PT78704&lang=en

last modified: 05/17/2018

