

PLUG-IN RELAY 3CO RELAY WITH LED 28MM,  
24V DC



General technical details:		
<b>Type of voltage</b>		DC
<b>Control supply voltage</b>		
• for DC / rated value		
• minimum	V	24
• maximum	V	24
<b>Number of NC contacts</b>		
• for auxiliary contacts		0
<b>Number of NO contacts</b>		
• for auxiliary contacts		0
<b>Number of changeover contacts</b>		
• for auxiliary contacts		3
<b>Operating current / of the auxiliary contacts</b>		
• at AC-15		
• at 230 V	A	5
<b>Design of the switching function</b>		changeover switch
• guided		No
<b>Switching behaviour</b>		monostable
Mechanical design:		
<b>Design of the electrical connection</b>		screw-type terminals

Design of the relay operating mechanism		poled
Product component / jumper socket		No
Width	mm	35.5
Height	mm	36.5
Depth	mm	69

#### Certificates/approvals:

General Product Approval

other



[Declaration of Conformity](#)

#### Further information:

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/industrial-controls/catalogs>

**Industry Mall (Online ordering system)**

<http://www.siemens.com/industrial-controls/mall>

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WW/view/en/LZX:MT323024/all>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=LZX:MT323024](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=LZX:MT323024)

last change:

Jun 16, 2014